

	Type	L #	Hits	Search Text	DBs
1	BRS	L1	0	bump near3 (Sn37Pb)	USPAT
2	BRS	L2	37	bump near3 (Sn adj2 Pb)	USPAT
3	BRS	L3	23	bump near3 (Sn adj2 Pb)	US-PGP UB; EPO; JPO; DERWE NT; IBM_TD B
4	BRS	L4	3	(copper adj2 (layer or film)) near10 (copper adj2 stud)	USPAT
5	BRS	L5	4383	cu adj2 cu	USPAT
6	BRS	L6	16	5 same blm	USPAT
7	BRS	L7	7166	cu adj2 cu	US-PGP UB; EPO; JPO; DERWE NT; IBM_TD B
8	BRS	L8	5	7 and blm	US-PGP UB; EPO; JPO; DERWE NT; IBM_TD B
9	BRS	L9	0	blm near10 NiV	USPAT
10	BRS	L10	0	blm same NiV	USPAT
11	BRS	L11	2	blm and NiV	USPAT
12	BRS	L12	4	blm and NiV	US-PGP UB; EPO; JPO; DERWE NT; IBM_TD B

US-PAT-NO: 6495449

DOCUMENT-IDENTIFIER: US 6495449 B1

TITLE: Multilayered diffusion barrier structure for improving  
adhesion property

----- KWIC -----

A method has been provided for improving the adhesion of copper to a nitrided metal diffusion barrier material, such as TiN, in an integrated circuit substrate. The method provided a multilayered diffusion barrier structure, comprising a nitrided metal diffusion barrier layer and an oxy-nitrided metal layer. The formation of an oxy-nitrided metal layer, instead of an oxide layer, permits the optimization of both contact resistance and adhesion property. The oxy-nitrided metal layer is formed either by the partial incorporation of oxygen into the nitrided metal diffusion barrier or by deposition in an oxygen ambient.

From thermodynamic arguments, good diffusion barriers for copper thus are those that have a positive heat of formation with copper. The nitrided metal diffusion barriers such as TiN, TaN, WN, TiSiN, TaSiN, WSiN, composed of mainly nitrogen and other metallic components such as Ti, Ta, W, offer the best conductive diffusion barrier property against copper diffusion. Copper nitrides have positive heats of formation so that it is thermodynamically unfavorable for copper to bond to nitrogen. These nitrides are more

thermodynamically stable than copper nitrides and thus are effective against copper bonding and diffusion. Of all the mentioned nitrides, TiN and WN are similar to each other. TaN is a somewhat better barrier than either TiN or WN, and thus adhesion of CVD copper to TaN is much more difficult to achieve than to TiN or WN. The adhesion property of copper to an effective diffusion barrier however is poor.

To improve the adhesion of the nitrided metal diffusion barrier to copper, it is imperative to change the surface properties of the nitrided metal diffusion barrier layer. This surface should contain materials that bond with copper. Thermodynamically, it means that the compound from reactions of this material and copper should have a negative heat of formation, such as a copper oxide. One way to change the surface properties of the nitrided metal diffusion barrier thus is to form an oxy-nitride layer on the surface by oxy-nitriding the nitrided metal diffusion barrier layer surface, and the presence of oxygen in the oxy-nitride layer would promote the adhesion of copper to the diffusion barrier. The oxy-nitride layer comprises the metal, nitrogen, and oxygen, and serves to improve the adhesion of the multilayered diffusion barrier structure to the subsequently deposited layer. As oxygen is incorporated into the nitrided metal diffusion barrier surface, the surface becomes an oxy-nitrided metal, and no longer has the strong diffusion barrier property. This surface thus exhibits strong chemical bonding with the subsequent deposited layer. Furthermore, this thin oxy-nitrided layer is conductive and thus the contact resistance is reduced. The amount of oxygen in the oxy-nitride layer however has a strong affect on the contact resistance.

The oxidizing condition will produce an oxide layer, however thin, that raises the contact resistance because of its non conductive property. Care should be taken to avoid the extreme case of oxidizing the nitrided metal diffusion barrier that occurs by introducing an excessive amount of oxygen. One way to avoid over-oxidizing the nitrided metal barrier surface is to introduce a small amount of oxy-nitride contained gas or a precursor that contains oxygen and nitrogen to the barrier surface. The introduction of the oxy-nitride or oxygen-nitrogen combination reduces oxidizing of the surface. Therefore a method to improve the adhesion of the nitrided metal diffusion barrier without introducing a non-conductive oxide layer is to have a multilayer: a nitrided metal diffusion barrier layer to block foreign material diffusion, and a thin oxy-nitrided metal layer to provide the adhesion property. The oxygen content in this oxy-nitrided layer is small such that the nitrided metal layer is not oxidized and results in a non-conductive layer.

In the oxy-nitriding process, the metal comes from the nitrided metal diffusion barrier layer, oxygen comes from the ambient, and nitrogen can be from the nitrided metal diffusion barrier layer and the ambient. There are different ways of incorporating the metal, oxygen, nitrogen to form the oxy-nitride layer. One way is to introduce a small amount of oxygen to a thin surface of the nitrided metal diffusion barrier. To provide a thin oxy-nitrided metal layer such as TiON, TiSiON, TaON, TaSiON, WON, WSiON, the nitrided metal diffusion barrier surface is oxy-nitrided in an oxygen-contained ambient. The oxy-nitrided metal adhesion property improvement is most effective with TiN, a less effective diffusion barrier, and much less effective with TaN, a more effective diffusion barrier. This method uses the nitrogen

from the nitrided diffusion barrier layer. Another way is to introduce oxygen and nitrogen from an ambient. Additional nitrogen thus comes from the ambient source. Another way is to deposit a thin oxy-nitride metal diffusion barrier layer by using an oxygen/nitrogen precursor together with the precursors needed to deposit the nitrided metal diffusion barrier. Not all oxy-nitrided materials however exhibit good adhesion property.

An improved method to improve adhesion is to form a multilayer: a nitrided metal diffusion barrier layer and a thin oxy-nitride metal layer. The thin oxy-nitride metal layer comprises the metal, nitrogen, and oxygen, hence the name oxy-nitride metal, the oxygen species being less than the nitrogen species, that works best since it is much more conductive than an oxide, and the adhesion property does not differ significantly.

Accordingly, a method to improve the adhesion property of copper to the nitrided metal diffusion barriers such as TiN, TiSiN, TaN, TaSiN, WN, WSiN, by forming a multilayered diffusion barrier structure is provided. The provided multilayered diffusion barrier is deposited on an underlayer, and provides improved adhesion to a subsequently deposited layer. The method comprises the steps of: a) Depositing a nitrided metal diffusion barrier layer on the underlayer in a diffusion barrier deposition equipment, whereby this diffusion barrier layer serves as a barrier between the underlayer and the subsequently deposited layer; b) Forming a thin metal nitrogen-rich oxy-nitride layer by oxy-nitriding the diffusion barrier material surface, this oxy-nitride layer comprises the metal, nitrogen, and oxygen, the oxygen species being less than the nitrogen species, whereby this layer serves to improve the adhesion of

the  
multilayered diffusion barrier structure to the subsequently deposited  
layer.

The two layers: nitrided metal diffusion barrier layer and the  
oxy-nitrided  
metal layer are formed in sequence. The method includes the formation of  
these  
two layers in two separate locations: two process chambers in the same  
process  
equipment, or in two separate process equipment. The formation of the  
nitrided  
metal diffusion barrier will occur in the first process chamber (of the two  
chamber equipment), or in the first process equipment. The substrate will  
then  
be moved to the second process chamber (of the two chamber equipment),  
or to  
the second process equipment for the oxy-nitriding process. The  
oxy-nitriding  
process to form the oxy-nitrided metal layer will require an  
oxygen-contained  
ambient. In some aspects of the invention, an elevated temperature is also  
provided. The elevated temperature ranges from 200.degree. C. to  
1200.degree.  
C., with 300-500.degree. C. being a typical temperature range. The  
oxy-nitriding time ranges from a few seconds to several minutes, depending  
on  
many factors such as the optimization of process flow, the optimization of  
the  
desired level of adhesion, the optimization of contact resistance, etc.

In some aspects of the invention, the nitrided metal diffusion barrier is  
selected from a group consisting of TiN, TiSiN, TaN, TaSiN, WN, WSiN.

The method also provides the thickness of the oxy-nitride layer on the  
surface of nitrided metal diffusion barrier to be less than 5 nm. The 5 nm

thick or less metal oxy-nitride layer offers adequate adhesion, and does not increase much the overall thickness of the multilayered diffusion barrier structure. Some applications, such as the ones in advanced semiconductor processing, require that the overall diffusion barrier thickness to be less than 50 nm, so a thin metal oxy-nitride layer is desirable, provided that adequate adhesion is achieved.

The method also provides various techniques to deposit the nitrided metal diffusion barrier. The evaporation technique can deliver the nitrided metal diffusion barrier by heating the source material. The sputtering technique can deliver the nitrided metal diffusion barrier by sputtering a target in a nitrogen-contained ambient. TiN diffusion barrier can be formed using a Ti target. Or by using a TiN target, the sputtering technique can deliver TiN without the need for the additional nitrogen ambient. The sputtering technique however does not fill the gap very well. The chemical vapor deposition technique can deliver the nitrided metal diffusion barrier by using appropriate precursors. Typical TiN liquid precursors are tetrakisdimethylaminetitanium (TDMAT), tetrakisdiethylaminetitanium (TDEAT), and tetrakismethylethylaminetitanium (TMEAT). These precursors can be combined with a nitrogen source such as ammonia ( $\text{NH}_3$ ), or nitrogen. Typical TaN liquid precursors include pentadiethylaminetantalum (PDMAT), that can be used with or without a nitrogen source. Typical WN chemical vapor deposition uses a precursor such as  $\text{WF}_6$  with nitrogen. The addition of other materials such as silicon can produce ternary nitrided metal diffusion barriers such as  $\text{TiSiN}$ ,  $\text{TaSiN}$ , or  $\text{WSiN}$ . To further excite the precursors, additional energies from a plasma source can be added as in the technique of plasma-enhanced chemical vapor deposition.

The method also provides various oxygen-contained ambient. To provide a thin oxy-nitrided metal layer, an ambient comprising the oxygen species is needed. The oxygen species can be oxygen gas,  $N_2O$ ,  $NO_2$  gas, water vapor, alcohol vapor, OH ligand, chemicals containing OH ligand, chemicals releasing OH ligand upon high temperature annealing. The oxygen species can also be diluted in other gases.

The method also provides the reactive oxygen species by plasma source to oxy-nitriding the nitrided metal diffusion barrier layer. The plasma source can be a direct plasma source or a downstream plasma source. In some aspects of the invention, the nitrided metal diffusion barrier is deposited by plasma-enhanced chemical vapor deposition. In this case, the underlayer is exposed to plasma energies of the diffusion barrier precursors. At the end of the deposition, the diffusion barrier precursors are turned off, and an oxygen-contained ambient is introduced. The presence of the oxygen plasma will incorporate some oxygen into the nitrided metal diffusion barrier to form the metal oxy-nitride metal layer. As mentioned earlier, care should be taken to avoid oxidizing the nitrided metal diffusion barrier.

The method also provides an alternate way to oxy-nitriding the nitrided metal diffusion barrier layer. In the case of the high temperature nitrided metal diffusion barrier deposition process, the oxy-nitriding process occurs during the cooling down period of the diffusion barrier formation. The oxy-nitriding process is then independent of time, i.e. self-limiting, and requires no external heating source, i.e. self-annealing process. A preferred method to achieve this process is to move quickly the deposited hot nitrided metal diffusion barrier to an oxygen-contained ambient where the nitrided metal diffusion barrier is annealed in an oxygen-contained ambient by its own



||    ||                 |                 |                 |                 |                 |

1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48 49 50 51 52 53 54 55 56 57 58 59 60 61 62 63 64 65 66 67 68 69 70 71 72 73 74 75 76 77 78 79 80 81 82 83 84 85 86 87 88 89 90 91 92 93 94 95 96 97 98 99 100

1

|||                      |                      |                      ||                      |                      ||                      |||

## Discussion

[illegible]

1 1 1 1 1

1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48 49 50 51 52 53 54 55 56 57 58 59 60 61 62 63 64 65 66 67 68 69 70 71 72 73 74 75 76 77 78 79 80 81 82 83 84 85 86 87 88 89 90 91 92 93 94 95 96 97 98 99 100 101 102 103 104 105 106 107 108 109 110 111 112 113 114 115 116 117 118 119 120 121 122 123 124 125 126 127 128 129 130 131 132 133 134 135 136 137 138 139 140 141 142 143 144 145 146 147 148 149 150 151 152 153 154 155 156 157 158 159 160 161 162 163 164 165 166 167 168 169 170 171 172 173 174 175 176 177 178 179 180 181 182 183 184 185 186 187 188 189 190 191 192 193 194 195 196 197 198 199 200 201 202 203 204 205 206 207 208 209 210 211 212 213 214 215 216 217 218 219 220 221 222 223 224 225 226 227 228 229 230 231 232 233 234 235 236 237 238 239 240 241 242 243 244 245 246 247 248 249 250 251 252 253 254 255 256 257 258 259 260 261 262 263 264 265 266 267 268 269 270 271 272 273 274 275 276 277 278 279 280 281 282 283 284 285 286 287 288 289 290 291 292 293 294 295 296 297 298 299 300 301 302 303 304 305 306 307 308 309 310 311 312 313 314 315 316 317 318 319 320 321 322 323 324 325 326 327 328 329 330 331 332 333 334 335 336 337 338 339 340 341 342 343 344 345 346 347 348 349 350 351 352 353 354 355 356 357 358 359 360 361 362 363 364 365 366 367 368 369 370 371 372 373 374 375 376 377 378 379 380 381 382 383 384 385 386 387 388 389 390 391 392 393 394 395 396 397 398 399 400 401 402 403 404 405 406 407 408 409 410 411 412 413 414 415 416 417 418 419 420 421 422 423 424 425 426 427 428 429 430 431 432 433 434 435 436 437 438 439 440 441 442 443 444 445 446 447 448 449 450 451 452 453 454 455 456 457 458 459 460 461 462 463 464 465 466 467 468 469 470 471 472 473 474 475 476 477 478 479 480 481 482 483 484 485 486 487 488 489 490 491 492 493 494 495 496 497 498 499 500 501 502 503 504 505 506 507 508 509 510 511 512 513 514 515 516 517 518 519 520 521 522 523 524 525 526 527 528 529 530 531 532 533 534 535 536 537 538 539 540 541 542 543 544 545 546 547 548 549 550 551 552 553 554 555 556 557 558 559 560 561 562 563 564 565 566 567 568 569 570 571 572 573 574 575 576 577 578 579 580 581 582 583 584 585 586 587 588 589 590 591 592 593 594 595 596 597 598 599 600 601 602 603 604 605 606 607 608 609 610 611 612 613 614 615 616 617 618 619 620 621 622 623 624 625 626 627 628 629 630 631 632 633 634 635 636 637 638 639 640 641 642 643 644 645 646 647 648 649 650 651 652 653 654 655 656 657 658 659 660 661 662 663 664 665 666 667 668 669 670 671 672 673 674 675 676 677 678 679 680 681 682 683 684 685 686 687 688 689 690 691 692 693 694 695 696 697 698 699 700 701 702 703 704 705 706 707 708 709 710 711 712 713 714 715 716 717 718 719 720 721 722 723 724 725 726 727 728 729 730 731 732 733 734 735 736 737 738 739 740 741 742 743 744 745 746 747 748 749 750 751 752 753 754 755 756 757 758 759 760 761 762 763 764 765 766 767 768 769 770 771 772 773 774 775 776 777 778 779 780 781 782 783 784 785 786 787 788 789 790 791 792 793 794 795 796 797 798 799 800 801 802 803 804 805 806 807 808 809 810 811 812 813 814 815 816 817 818 819 820 821 822 823 824 825 826 827 828 829 830 831 832 833 834 835 836 837 838 839 840 841 842 843 844 845 846 847 848 849 850 851 852 853 854 855 856 857 858 859 860 861 862 863 864 865 866 867 868 869 870 871 872 873 874 875 876 877 878 879 880 881 882 883 884 885 886 887 888 889 890 891 892 893 894 895 896 897 898 899 900 901 902 903 904 905 906 907 908 909 910 911 912 913 914 915 916 917 918 919 920 921 922 923 924 925 926 927 928 929 930 931 932 933 934 935 936 937 938 939 940 941 942 943 944 945 946 947 948 949 950 951 952 953 954 955 956 957 958 959 960 961 962 963 964 965 966 967 968 969 970 971 972 973 974 975 976 977 978 979 980 981 982 983 984 985 986 987 988 989 990 991 992 993 994 995 996 997 998 999 1000 1001 1002 1003 1004 1005 1006 1007 1008 1009 1010 1011 1012 1013 1014 1015 1016 1017 1018 1019 1020 1021 1022 1023 1024 1025 1026 1027 1028 1029 1030 1031 1032 1033 1034 1035 1036 1037 1038 1039 104

||| |

11      111      1111      1      111      1      11

1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48 49 50 51 52 53 54 55 56 57 58 59 60 61 62 63 64 65 66 67 68 69 70 71 72 73 74 75 76 77 78 79 80 81 82 83 84 85 86 87 88 89 90 91 92 93 94 95 96 97 98 99 100

1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48 49 50 51 52 53 54 55 56 57 58 59 60 61 62 63 64 65 66 67 68 69 70 71 72 73 74 75 76 77 78 79 80 81 82 83 84 85 86 87 88 89 90 91 92 93 94 95 96 97 98 99 100

1 2 3

1 0 0 1